



Van den Hul MM - 2, Phono Cartridge

Discontinued. Retipping service remains available.

Description:

Moving magnet cartridge with the more accurate tracking VDH-type 1 tip, boron cantilever and 5.6 mV/channel.

Specifications:

Cartridge Type	MM - 2	Unit
Stylus Replacement Available	MM - 2R	
Stylus Shape	VDH - I	
Stylus Radii	3 x 85	Micron
Frequency Range	10 - 25.000	Hz
Tracking Force	7.5 - 12.5	mN
Static Compliance	40	Micron / mN
Tracking Ability at 15 mN at 315 Hz	70 - 80	Micron
Output Voltage at 1 kHz at 5.7 cm/s eff.	5.6	mV RMS
Channel Unbalance	< 1.0	dB
Channel Separation at 1 kHz/10 kHz	>30 / >24	dB
Equivalent Stylus Tip Mass	0.45	Milligram
System Weight	6.5	Gram
Vertical Tracking Angle	22	Degrees
Coil Inductance	400	mH
Optimum Load Capacitance	300	pF
Recommended Load Impedance	47k	Ohm
Recommended Eff. Tone arm Mass	8 - 12	Gram

While A.J. van den Hul B.V. provides the information contained in this document to anyone, we retain (joint) copyright and/or publication rights on all text and graphic images. This means that:

You MAY NOT: Modify or re-use the text and graphics, distribute the text and graphics to others, or "mirror" this document's information on another server without the written permission of A.J. van den Hul B.V.

You MAY: Store the document on your own computer for your own personal use, print copies of the information for your own personal use, and refer to it in your own documents or on your website.

A.J. van den Hul B.V. reserves all other rights and is not to be held liable for the contents of this document.

www.vandenhul.com